



WILLIAMS FIRE & HAZARD CONTROL®
T-STORM® NFF 3x3 UL201 Non-Fluorinated
Alcohol Resistant Firefighting Foam Concentrate



The power behind **your mission**



Redefining Performance

The latest addition to the WILLIAMS FIRE & HAZARD CONTROL® firefighting foam portfolio is our new T-STORM non-fluorinated 3x3 foam concentrate for use on both polar solvent and hydrocarbon fuel fires.

Setting a New Standard

Introducing the patent-pending technology of T-STORM NFF 3x3 UL201 foam concentrate which sets a new standard for non-fluorinated Class B firefighting foams:

- Independent, 3rd-party verified to achieve the same application rate as a UL 162 listed Alcohol Resistant Aqueous Film-Forming Foam for control and extinguishment of hydrocarbon fuel fires
- Effective control and suppression on hydrocarbon fuel fires at expansion ratios as low as 3 to 1 – supporting utilization of standard, non-aspirated nozzles and hand-lines for many applications
- Viscosity similar to a quality 3x3 AR-AFFF, enabling application with most properly-calibrated proportioning and discharge response devices and reducing the need for significant hardware changes
- Class-leading, cross-functional performance for fire knock-down and control; long-lasting foam blanket for extended post-extinguishment burn-back resistance and vapor suppression
- Flexible response with 3% proportioning in fresh, brackish, or salt water for both hydrocarbon and polar solvent Class B hazards

This isn't a lightweight AFFF product.

This isn't a mandate to change foam firefighting response hardware.

This isn't an untested experiment.

This isn't a non-compliant product from a no-name startup.

This isn't a concession.

This is Non-Fluorinated Foam Fire Suppression: Redefined.



T-STORM NFF 3x3 UL201 firefighting foam concentrate is UL listed with various proportioners, nozzles, and other discharge devices. Consult the UL listing for complete details.

This foam is well-suited for use in applications such as:

- Municipal and Industrial Response for spill and limited scale Type III hazards
- Foam systems with Type II discharge devices

T-STORM NFF 3x3 UL201 concentrate is defined as a non-fluorinated firefighting foam concentrate, produced in equipment free from the use of PFAS chemistry. Since this product is free from any intentionally added PFAS chemistry and precautions have been taken to avoid PFAS contamination, it inherently complies with Directives (EU) 2017/1000 on PFOA and 2019/1021 (EU POPs directive) as a non-fluorinated product.

Industry Leading Performance

Like all non-fluorinated firefighting foam concentrates, T-STORM NFF 3x3 UL201 foam concentrate is UL 162 tested and listed as a Synthetic Foam. Per this UL standard, the minimum design application rate for this foam is 0.16 gpm/ft² (6.5 lpm/m²) for Type III hydrocarbon fuel fires.



T-STORM NFF 3x3 UL201 Foam Application Rates gpm/ft ² (lpm/m ²)				
UL 162 Test Protocol for Type III Hydrocarbon - Forceful Application	Hydrocarbon Fuel		Premium Gasoline Fuel	
	Test Rate	Minimum Design Rate	Test Rate	Minimum Design Rate
	0.06 (2.4)	0.16 (6.5)		
UL 162 Synthetic Foam Test	0.06 (2.4)	0.16 (6.5)		
UL 162 AFFF Test (Witnessed by Independent 3rd Party)	0.04 (1.6)	0.10 (4.1)	0.06 (2.4)	0.16 (6.5)

In addition to the Synthetic Foam listing, this foam passed – under independent 3rd party witness – the much more challenging UL 162 Type III test protocol for an AFFF. This protocol utilizes a foam application test rate of 0.04 gpm/ft² (1.6 lpm/m²), which is 33% less than the application rate for the UL 162 Synthetic Foam test. Under this more challenging protocol, an AFFF with the same demonstrated performance as the NFF 3x3 UL201 foam would attain a minimum application design rate of 0.10 gpm/ft² (4.1 lpm/m²) for all Type III hydrocarbon fuel fires.

NFPA 11 requires a minimum design application rate of 0.10 gpm/ft² (4.1 lpm/m²) on hydrocarbon fuel spill fires,

and the 3rd party witnessed testing supports the use of T-STORM NFF 3x3 UL201 concentrate at this application rate.

NFPA 11 and UL 162 require a minimum design application rate of 0.16 gpm/ft² (6.5 lpm/m²) for non-fluorinated foams on Type III hydrocarbon fuel in depth fires. T-STORM NFF 3x3 UL201 foam has demonstrated an increased safety factor at this required application rate with its successful, witnessed test performance extinguishing Type III hydrocarbon fuel fires at the lower minimum application rate of an AFFF.

T-STORM NFF 3x3 UL201 performs well and is UL listed with E15 and several polar solvent fuels as well.

Foam Application Rates gpm/ft ² (lpm/m ²)			
T-STORM NFF 3x3 UL201 Foam UL 162 Synthetic Foam Application Listing*		Test Rate	Minimum Design Rate
Type III Hydrocarbon - Forceful Application	Hydrocarbons	0.06 (2.4)	0.16 (6.5)
	E15 (15% Ethanol/85% Gasoline)	0.10 (4.1)	0.17 (6.9)
Type II Hydrocarbon - Gentle Application	Hydrocarbons	0.06 (2.4)	0.10 (4.1)
Type II Polar Fuels - Gentle Application	Alcohols	0.10 (4.1)	0.17 (6.9)
	Ethanol	0.06 (2.4)	0.10 (4.1)
	Ketones	0.10 (4.1)	0.17 (6.9)
	E85 (85% Ethanol/15% Gasoline)	0.09 (3.7)	0.15 (6.1)

* Refer to UL Product iQ directory for complete listing details.

Note: If any foam product is discharged into the environment, efforts should be made to control, contain and collect the discharge for proper disposal, while following all applicable laws, regulations, and codes. Further information regarding the use, discharge, and disposal of firefighting foams can be found at www.williamsfire.com.

About Johnson Controls

At Johnson Controls, we transform the environments where people live, work, learn and play. From optimizing building performance to improving safety and enhancing comfort, we drive the outcomes that matter most. We deliver our promise in industries such as healthcare, education, data centers and manufacturing. With a global team of 105,000 experts in more than 150 countries and over 130 years of innovation, we are the power behind our customers' mission. Our leading portfolio of building technology and solutions includes some of the most trusted names in the industry, such as Tyco®, York®, Metasys®, Ruskin®, Titus®, Frick®, Penn®, Sabroe®, Simplex®, and Grinnell®.

For more information, contact your regional WILLIAMS FIRE & HAZARD CONTROL® product representative or visit www.williamsfire.com.

Australia

Johnson Controls
Level 1, 13B Compark Circuit
Mulgrave, VIC 3170
Australia
Tel: +61 1300 725 688
FSP.InsideSales.ANZ@jci.com

Singapore

Johnson Controls
2 Serangoon North Avenue 5
#07-01 Singapore 554911
Tel: +65 6577 4360
FSP.InsideSales.SG@jci.com

United States

Johnson Controls
9605 Richard Wycoff Drive
Port Arthur, TX 77640
Tel: +1-409-971-4100
24 HR Emergency Tel: +1-409-727-2347

Italy

Johnson Controls
Viale Padania 3
24055 Cologno Al Serio (BG)
Italy
Tel: +39 035 2057011
FSP.InsideSales.Milan@jci.com

United Arab Emirates

Johnson Controls
API World Tower
Sheikh Zayed
Dubai
United Arab Emirates
PO Box 502937
Tel: +971 4 309 9999
FSP.InsideSales.AE@jci.com